



Main

Range	Clipsal
Product or component type	Floodlight
Device application	Lighting

Complementary

Type of installation	Outdoor
Device mounting	Surface
Total system power	50 W
Light source	LED
[Ue] rated operational voltage	240 V AC 50 Hz
Luminous flux	4500 lm
Colour rendering index	R _a =70
Bulb lifespan	30000 h
Colour temperature	4000 K
Beam angle	100 °
Electrical insulation class	Class I
Height	Body with trunion arm: 155 mm
Width	210 mm
Depth	33 mm
Net weight	1.45 kg
Cable length	0.9 m

Environment

IP degree of protection	IP65
Ambient air temperature for operation	-10...40 °C
Relative humidity	10...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.0 cm
Package 1 Width	3.0 cm
Package 1 Length	21.0 cm
Package 1 Weight	1.7 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	23.6 cm

Package 2 Width	24.8 cm
Package 2 Length	52.0 cm
Package 2 Weight	11.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	3-Years
----------	---------