

Product data sheet

Characteristics

2036CC4-WE

Room Access Card Operated Switch 2000 Series - 250 V - 1 x 16 A and 3 x 10 A - White Electric



Main

Range of product	Series 2000
Product brand	Clipsal
Device presentation	Basic element with full cover plate

Complementary

Local signalling	without
[Ue] rated operational voltage	250 V AC
Rated current	16 A
Marking	Without marking
Actuator	Room access card

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.126 kg
Package 1 Height	3.5 cm
Package 1 width	7.6 cm
Package 1 Length	11.6 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Weight	14.0 kg
Package 2 Height	30.5 cm
Package 2 width	29.6 cm
Package 2 Length	43.6 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	0.694 kg
Package 3 Height	11.9 cm
Package 3 width	8.3 cm
Package 3 Length	17.9 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile