

## Product data sheet

### Characteristics

# 230MIC163

Meter Box, Clipsal Resi MAX, Isolator With 1 Pole 63A C Curve MCB enclosure and lock off device

#### Main

Product brand	Clipsal
---------------	---------

#### Complementary

Curve code	C
Number of poles	1
[In] rated current	63 A
Breaking capacity	6 kA conforming to EN 60898

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	10.2 cm
Package 1 Length	20.2 cm
Package 1 Weight	419 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	19 cm
Package 2 Width	20.3 cm
Package 2 Length	47.5 cm
Package 2 Weight	5.526 kg

#### Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	No
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Circularity Profile	No need of specific recycling operations
Take-back	No
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.