

Product data sheet

Characteristics

230MIC163

Clipsal Resi MAX Meter Isolator With 1 Pole
63A C Curve MCB enclosure and lock off
device



Main

Product brand	Clipsal
---------------	---------


Complementary

Curve code	C
Number of poles	1
[In] rated current	63 A
Breaking capacity	6 kA conforming to EN 60898

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	10.2 cm
Package 1 Length	20.2 cm
Package 1 Weight	419 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	19 cm
Package 2 Width	20.3 cm
Package 2 Length	47.5 cm
Package 2 Weight	5.526 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
-------------------	--

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.