

Product data sheet Characteristics

30MD2-WE

Device presentation

Clipsal - Mechanisms, Switch Mechanisms, 30 Series, 250V 10A - 2 Way, Double Pole, Double Throw





Main Range of product Series 30 Standard Series Product brand Clipsal

Basic element

Complementary

Switch function	2-way
Number of rocker	1
Number of poles	2
Device mounting	Flush
Local signalling	without
[Ue] rated operational voltage	250 V AC
Rated current	10 A
Load type	Fluorescent 100 W 10 A LEDi lamp 100 W 10 A
Marking	Without marking
Actuator	Rocker

Packing Units

· coming or mo		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.2 cm	
Package 1 Width	2.5 cm	
Package 1 Length	3.5 cm	
Package 1 Weight	22 g	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.