

Product data sheet Characteristics

30USMSEN-WE

Clipsal - Mechanisms, Switch Mechanism, 1/2W 20A 16AX -Sensor



Main

Range of product	Series 30 Standard Series
Product brand	Clipsal
Device presentation	Basic element

Complementary

Switch function	2-way 1-way	
Number of rocker	1	
Device mounting	Flush	
Local signalling	without	
[Ue] rated operational voltage	250 V AC	
Rated current	20 A 16 AX, fluorescent lamp	
Marking	Sensor	
Marking location	Marking on surface	
Actuator	Rocker	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.016 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.