

Product data sheet Characteristics

41E350PBT2SM-VW

Clipsal Iconic, Electronic Time Delay Switch MechanismPushButton with ControlLink, 2-Wire 350W





Main

Range	Clipsal Iconic	
Product or component type	Timer	
Device presentation	Mechanism	

Complementary

Device mounting	Flush
Actuator	Push-button
Fixing mode	Locking bar
Colour tint	Vivid white
Surface finish	Matt
Type of packing	Вох
Sale per indivisible quantity	1
Type of operator	Momentary
Time delay	30 s 1 min 5 min 15 minutes 30 minutes 1 h 2 h 4 h
Remote control type	Push-button
[Ue] rated operational voltage	240 V AC 50 Hz
Load type	Incandescent lamp 350 W Medium voltage halogen lamp 350 W Low voltage halogen lamp with iron core transformer 350 W Linear fluorescent ballast 250 W Compact fluorescent load 250 W Dimmable LED lighting driver 350 W LED lighting driver (non-dimmable) 250 W Resistive 350 W
Power range	> 10 W
Derating factor	1 devices(350 W) without derating 2 devices(250 W) with derating factor 3 devices(220 W) with derating factor 4 devices(175 W) with derating factor 5 devices(120 W) with derating factor 6 devices(100 W) with derating factor
Operating distance	30 m
Control signal type	ControlLink

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Connections - terminals	Screw terminals
Number of terminals	3
Wiring configuration	2-wire
Screwdriver shape	Philips Square drive no 1 (SQ1)
Local signalling	LED indicator (warm white)
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	23.5 mm
Width	23.5 mm
Depth	42 mm
Embedding depth	39 mm
Standards	AS/NZS 60669.2.1

Environment

Ambient air temperature for storage	060 °C
Ambient air temperature for operation	045 °C
Relative humidity	090 %

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.1 cm	
Package 1 Width	6.9 cm	
Package 1 Length	8.7 cm	
Package 1 Weight	67 g	

Offer Sustainability

- · · · · · · · · · · · · · · · · · · ·		
Sustainable offer status	Green Premium product	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

Life Is On