

Product data sheet

Characteristics

4CB110/10

Miniature circuit breaker, MAX4, 1P, 10 A, C curve, 10000 A, 240 V



Main

| | |
|---------------|---------|
| Product brand | Clipsal |
|---------------|---------|

Complementary

| | |
|--------------------------------|--|
| Curve code | C |
| Number of poles | 1 |
| [In] rated current | 10 A |
| Number of modules | 1 |
| [Ue] rated operational voltage | 240 V |
| Breaking capacity | 10 kA conforming to EN 60898 |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Mechanical durability | 20000 cycles |
| Electrical durability | 20000 cycles |
| Connections - terminals | Screw terminal for 1 cable(s) 0.75...16 mm ² rigid Screw terminal for 1 cable(s) 0.33...10 mm ² flexible Screw terminal for 1 cable(s) 0.33...10 mm ² flexible with ferrule |
| Wire stripping length | 13 mm |
| Tightening torque | 2 N.m |

Environment

| | |
|---------------------------------------|--|
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Standards | AS/NZS 60898 |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Height | 81 mm |
| Width | 18 mm |
| Depth | 78.5 mm |
| Net weight | 115 g |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------|-----------|
| Package 1 Weight | 102.000 g |
| Package 1 Height | 72.000 mm |
| Package 1 width | 20.000 mm |
| Package 1 Length | 85.000 mm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |