

Product data sheet

Characteristics

4PS40COA

Clipsal MAX4, Change over switch 1P 40 A
415 V Auto off manual



Main

| | |
|------------------|----------|
| Range of product | Series 4 |
| Product brand | Clipsal |

Complementary

| | |
|--------------------------------|---------------------|
| Product or component type | Switch disconnecter |
| [Ue] rated operational voltage | <= 415 V AC |
| [In] rated current | 40 A |
| Number of poles | 1 |
| Mounting support | DIN rail |
| Marking | AUTO-OFF-MANUAL |

Environment

| | |
|-------------------------|------------------|
| IP degree of protection | Front face: IP20 |
|-------------------------|------------------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.1 cm |
| Package 1 Width | 9.1 cm |
| Package 1 Length | 7.5 cm |
| Package 1 Weight | 102.8 g |

Offer Sustainability

| | |
|---------------------|--|
| EU RoHS Directive | Under investigation |
| Circularity Profile | No need of specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.