

## Product data sheet

### Characteristics

# 56C320FLE-GY

56 Series Switched Socket Outlet- 20A- 3 Pin-  
1P- 250V - Less Enclosure - Grey



#### Main

Range	Clipsal - 56 Series
Product or component type	Switched socket
Device application	Power supply
Colour	Grey (RAL 7035)

#### Complementary

Plug, socket category	Low voltage
Outlet standard	Australian/New Zealand
Plug, socket, control station shape	Angled Straight
[In] rated current	20 A
[Ue] rated operational voltage	250 V AC 50 Hz
Poles description	1P + N + E
Protection type	Without protection
Material	Polycarbonate: cover
Contacts material	Pins: phosphor bronze
Connections - terminals	Screw terminal cable(s) 2.5...6 mm <sup>2</sup>
Mounting mode	Surface mounted
Outlet standard	Industrial
Depth	72 mm
Width	101 mm
Height	204 mm
Net weight	1.2 kg
Targeted country	Australia

#### Environment

Standards	AS/NZS 3123
Ambient air temperature for operation	-25...75 °C
IP degree of protection	IP66 conforming to AS 60529

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.4 cm
Package 1 Width	10.1 cm
Package 1 Length	7.2 cm
Package 1 Weight	1 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>