

Product data sheet Characteristics

56K1SW350LE-GY

Clipsal - 56 Series, Surface Switch, IP66 3 Pole 50A Key Less Enclosure





Main

Widin	
Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Switch
Device presentation	Basic element with full cover plate
Device application	Control
Colour	Cover: grey
Colour Handle colour	Cover: grey Grey

Complementary

Switch function	3-pole
Poles description	3P
Control type	Rotary knob
Number of poles	3
Device mounting	Surface
Material	PC (polycarbonate)
Tightening torque	0.8 N.m
Local signalling	without
[Ue] rated operational voltage	500 V AC 50 Hz
Rated current	50 A
Marking	ON-OFF
Marking location	Marking on surface
Height	107 mm
Width	101 mm
Depth	76 mm
Net weight	0.6 kg
Breaking capacity	50 kA
Targeted country	Australia
Rotary handle padlocking	2 padlocks 8 mm
Actuator	Key
Motor M-rating AS3133	M200 at 500 V

Environment

Ambient air temperature for operation	-2575 °C	
IP degree of protection	IP66 conforming to AS 60529	
Standards	AS/NZS 3133	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	10.7 cm	
Package 1 Width	10.1 cm	
Package 1 Length	7.6 cm	
Package 1 Weight	0.6 kg	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	