Product data sheet Characteristics

56SW132LE-RO

Clipsal - 56 Series, Surface Switch, PVC IP66 1 Gang 32A Less Enclosure



Main Range of product Series 56 Range Clipsal - 56 Series Product brand Clipsal Switch Product or component type Basic element with full cover plate Device presentation Device application Control Cover: orange Colour

Grey

Yes

Complementary

1	
Switch function	1-pole
Poles description	1P
[lcm] rated short-circuit making capacity	1 kA
Control type	Rotary knob
Number of poles	1
Device mounting	Surface
Material	PC (polycarbonate)
Tightening torque	0.8 N.m
Local signalling	without
[Ue] rated operational voltage	250 V AC 50 Hz
Rated current	32 A
Marking	ON-OFF
Marking location	Marking on surface
Height	107 mm
Width	101 mm
Depth	72 mm
Net weight	0.18 kg
Breaking capacity	32 kA
Targeted country	Australia
Rotary handle padlocking	2 padlocks 8 mm
[lcw] rated short-time withstand current	1.2 kA for 1 s
[Uimp] rated impulse withstand voltage	4 kV
Motor M-rating AS3133	M180 at 250 V

Handle colour

Suitability for isolation

Environment

Ambient air temperature for operation	-2575 °C
IP degree of protection	IP66 conforming to AS 60529
Standards	AS/NZS 3133

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.18 kg

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	

Life Is On