

## Product data sheet Characteristics

# 752/CU

C-Bus Control and Management System, Occupancy Controller Range, Ceiling Ultrasonic Motion Detector, 360 Degree



#### Main

Range	C-Bus	
Product brand	Clipsal	

### Complementary

[Us] rated supply voltage	24 V DC	
Network type	DC	
Number output current	<= 280 mA	

#### Packing Units

r acking critis		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8 cm	
Package 1 Width	13 cm	
Package 1 Length	13 cm	
Package 1 Weight	250 g	

### Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.