### Product data sheet Characteristics

## **755WSA**

## Clipsal - Smoke Alarms, Smoke Alarm, Wiser, 230V, IP20, White





# Main

Wilding	
Range of product	Wiser
Range	Wiser
Product brand	Schneider Electric
Concentrator compatibility	Wiser hub generation 1
Product or component type	Smoke detector
Device application	Early detection of smouldering fires and open fires
Mobile App name	Wiser by SE
Electronic sensor type	Photo-electric sensor
Type of packing	Carton

Complementary

White (RAL 9003)
Mains
220240 V AC 50/60 Hz
Wireless Zigbee (2.4 GHz), 2.5 mW at < 50 m
Heat
Local alarm
Scattered light (Tyndall effect)
Smoke
Button (test/hush function)
40 for wireless alarm
50 m indoor
85 dB at 3 m, minimum
10 min (hush)
Visual: 1 LED (red) for warning and low battery
Screw terminal (back of the device) - 2 x 1.5 mm <sup>2</sup>
Thermoplastic
Indoor
Surface
Ceiling
By screws
140 mm
45.9 mm

### Environment

IP degree of protection	IP20
Ambient air temperature for operation	045 °C
Ambient air temperature for storage	-2060 °C
Relative humidity	095 %
Product certifications	Activfire[RETURN]RCM
Standards	AS 3786

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	14 cm
Package 1 Length	15 cm
Package 1 Weight	436 g
Unit Type of Package 2	S04
Number of Units in Package 2	24
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	12.464 kg
Unit Type of Package 3	P12
Number of Units in Package 3	288
Package 3 Height	105 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	164.568 kg

### Offer Sustainability

Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Life Is On