

Product data sheet Characteristics

A9E18325

Acti9, iIL double indicator light - Green/Red -110-230 Vac





Main

Range of product	Acti9
Product name	Acti9 iIL
Product or component type	Modular pilot ligth
Device short name	ilL
[Us] rated supply voltage	110230 V AC at 50/60 Hz 110130 V DC

Complementary

ed nmetrical DIN rail
nmetrical DIN rail
side: ProDis
mm
mm
5 mm
ite (RAL 9003)
nnel type terminal 1 cable(s) rigid 0.5 mm ² nnel type terminal 2 cable(s) rigid 2.5 mm ² nnel type terminal 1 cable(s) flexible 0.5 mm ² nnel type terminal 2 cable(s) flexible 2.5 mm ² nnel type terminal 2 cable(s) flexible with ferrule 2.5 mm ²
nm
l.m

Environment

Standards	IEC 60947-5-1	
IP degree of protection	IP2 IPxx B	
Pollution degree	2	
Tropicalisation	2	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for storage	-4080 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.6 cm
Package 1 Width	1.8 cm
Package 1 Length	8.2 cm
Package 1 Weight	45 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	7.8 cm
Package 2 Width	9.8 cm
Package 2 Length	23.3 cm
Package 2 Weight	602 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5.906 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts & cables product

Contractual warranty

Warranty	18 months	

Life Is On