Product data sheet
Characteristics

A9HC36S160
Acti9, MC metal DB - IP40 - 36 way fitted with 160A incomer

Main

Range	Acti9
Product or component type	Distribution board
Device application	Distribution
Colour	White (RAL 9003)
Provided equipment	Enclosure Removable gland plates at top and bottom of the enclosure Pan assembly Neutral bar Earthing bar Isolator
Door type	Plain

Complementary

Enclosure mounting	Surface
Protection device type	Main incomer: isolator - 160 A Outgoer: miniature circuit breaker (MCB) - 63 A Outgoer: residual current circuit breaker with overcurrent protection (RCBO) - 63 A
[Ie] rated operational current	160 A at 240/415 V AC
[Icw] rated short-time withstand current	25 kA for 100 ms
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Number of ways	36 ways
Enclosure/cubicle description	Single door enclosure
Enclosure material	Powder coated sheet steel
Height	916 mm external:
Width	470 mm external:
Depth	140 mm external:
Net weight	25 kg

Environment

Ambient air temperature for operation	-15…50 °C
IP degree of protection	IP40
Standards	AS/NZS 61439-3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	92.6 cm
Package 1 Width	48.0 cm
Package 1 Length	15.0 cm
Package 1 Weight	25.0 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Halogen content performance	Halogen free plastic parts product