

# Product data sheet Characteristics

# A9N21037

Acti9 - comb busbar - 1L+N with Aux and Vigi -9 mm pitch - 56 modules



Acti 9
Comb busbar
Connection accessory
1L + N
56

Complementary

Complementary	
Number of ways	22 ways Aux + N + 1 L + Vigi
Poles configuration for 1 way	1 x 1P + N
Connection pitch	9 mm between phase and neutral
Connector type	Tooth
Distance between way	45 mm
Marking	NL
Insulation	Insulated
Device presentation	Cuttable
[le] rated operational current	63 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	112
Width	1000 mm
Colour	Light grey (RAL 7035)
Range compatibility	Acti 9 C40 Acti 9 C40 Vigi Acti 9 DT40 Acti 9 DT40 Vigi Acti 9 DT40 Vigi Acti 9 iDPN Acti 9 iDPN Vigi Acti 9 iDPN Vigi Acti 9 ID C40 Acti 9 IDc Acti 9 ITG40 Multi 9 N40 Vigi

#### Environment

Standards	IEC 60947-7-1 IEC 61439-2	
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1	
Pollution degree	3 conforming to IEC 60947-7-1	
IP degree of protection	IP20 with end-pieces and tooth covers	

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	490.0 g
Package 1 Height	3 cm
Package 1 width	5 cm
Package 1 Length	97.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	40
Package 2 Weight	34.0 kg
Package 2 Height	30 cm
Package 2 width	80 cm
Package 2 Length	120 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	2.769 kg
Package 3 Height	107 cm
Package 3 width	10 cm
Package 3 Length	10 cm

### Offer Sustainability

REACh Declaration
Yes
Compliant EEU RoHS Declaration
Yes
Yes
€Yes
☑ China RoHS Declaration
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty 18 months	
--------------------	--

Life Is On

2