

## Product data sheet

### Characteristics

# ABL8BBU24400

Phaseo ABL7 ABL8, Battery control module,  
24..28.8V DC, 24V, 40A, for regulated SMPS



### Main

Range of product	Phaseo
Product or component type	Battery control module
Input voltage	24...28.8 V DC
Output voltage	(U <sub>battery</sub> -0.5) V in battery mode DC (U <sub>in</sub> -0.25) V in nominal mode DC
Maximum output current	40 A

### Complementary

Input voltage limits	22...30 V
Maximum power dissipation in W	12 W
Activation threshold	Adjustable 22...36 V
Number of output channels	1
Current consumption	0.6 A on load 0.1 mA no load ≤ 40.6 A
Output protection type	Against overload, protection technology: 1.5 x I <sub>n</sub> Against short-circuits, protection technology: battery-backed mode, automatic reset Against short-circuits, protection technology: power-supplied mode
Connections - terminals	For diagnostic relay: removable screw terminal block, connection capacity: 1 x 0.75 mm <sup>2</sup> For input connection: screw type terminals, connection capacity: 2 x 0.5...2 x 10 mm <sup>2</sup> AWG 20...AWG 8 For output connection: screw type terminals, connection capacity: 2 x 0.5...2 x 10 mm <sup>2</sup> AWG 20...AWG 8
Fixing mode	By clips on 35 mm symmetrical DIN rail, operating position: horizontal By clips on 35 mm symmetrical DIN rail, operating position: vertical
Marking	CE
Name of test	Electrostatic discharges conforming to IEC 61000-4-2 Emission conforming to IEC 61000-6-3 Induced electromagnetic field conforming to IEC 61000-4-6 level 3 Radiated electromagnetic field conforming to IEC 61000-4-3 level 3 Rapid transient conforming to IEC 61000-4-4 level 3 Surge conforming to IEC 61000-4-5 level 2 Conducted/radiated emissions conforming to EN 55022 class B, 20 %
Local signalling	1 C/O relay for alarm status 1 C/O relay for battery status 1 C/O relay for power supply status LCD screen for module status
Net weight	0.7 kg



## Environment

Product certifications	RCM[RETURN]EAC
Standards	UL 508 CSA C22.2 No 60950-1
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C
Environmental characteristic	EMC conforming to IEC 61000-6-3 EMC conforming to IEC 61000-6-2 Safety conforming to IEC 60950-1 Safety conforming to EN/IEC 61204-3
IP degree of protection	IP20 conforming to IEC 60529
Dielectric strength	500 V between input and ground 500 V between output and ground
Overvoltage category	Class II conforming to VDE 0106-1
Relative humidity	0...90 % during operation 0...95 % during storage
MTBF reliability	707945 H at 24 V DC with UTE C80-810 calculation method
Vibration resistance	2 gn (f= 11.9...150 Hz) conforming to IEC 61131-2 3.5 mm (f= 3...11.9 Hz) conforming to IEC 61131-2

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.2 cm
Package 1 Width	18 cm
Package 1 Length	18.5 cm
Package 1 Weight	1.349 kg
Unit Type of Package 2	S04
Number of Units in Package 2	8
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	12.11 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
PVC free	Yes


## Contractual warranty

Warranty	18 months
----------	-----------

24 Vdc/40 A Battery Control Module


Dimensions

mm  
inch




24 Vdc Battery Control Module

Mounting




24 Vdc Battery Control Module

Clearance



## 24 Vdc Battery Control Module

### Wiring Diagram



(1) See table below for the maximum unstored charge capacity (µF)

ABL	Max. Unstored Charge Capacity (µF)
8RPS24030	30 000
8RPS24050	50 000
8RPS24100	100 000
8RPM24200	100 000
8WPS24200	100 000
8WPS24400	100 000

## 24 Vdc Battery Control Module

### Outputs States (U = 24 Vdc: I > 5 mA, U = 230 Vac: I < 500 mA)

	No power from the power supply		Power from the power supply
	Alarm or device not supplied		No alarm
	No power from the battery pack		Power from the battery pack





### Inputs States (Dry Contact)

	Operational battery		Battery inhibited
--	---------------------	--	-------------------





### Wiring Requirements

## Cable Types and Wire Sizes

IEC / EN

		<b>ABL</b> <b>8RPS24030</b> <b>8RPS24050</b> <b>8RPS24100</b>	<b>ABL</b> <b>8RPM24200</b> <b>8WPS24200</b> <b>8WPS24400</b>
$\varnothing \leq 4 \text{ mm}^2$	$\varnothing > 4 \text{ mm}^2$		
<b>ABL 8BBU24200</b>	In + / -	1... 4 mm <sup>2</sup>	4... 10 mm <sup>2</sup>
	⏻ + / -	6 mm <sup>2</sup>	—
	Out + / -	6 mm <sup>2</sup>	—
<b>ABL 8BBU24400</b>	In + / -	1... 4 mm <sup>2</sup>	4... 10 mm <sup>2</sup>
	⏻ + / -	10 mm <sup>2</sup>	—
	Out + / -	10 mm <sup>2</sup>	—
		10 mm <sup>2</sup>	—
		—	—
		0, 14... 1 mm <sup>2</sup>	—

UL

		<b>ABL</b> <b>8RPS24030</b> <b>8RPS24050</b> <b>8RPS24100</b>	<b>ABL</b> <b>8RPM24200</b> <b>8WPS24200</b> <b>8WPS24400</b>
$\varnothing \leq 12 \text{ AWG}$	$\varnothing > 12 \text{ AWG}$		
<b>ABL 8BBU24200</b>	In + / -	16... 12 AWG	12... 6 AWG
	⏻ + / -	10 AWG	—
	Out + / -	10 AWG	—
<b>ABL 8BBU24400</b>	In + / -	16... 12 AWG	12... 6 AWG
	⏻ + / -	6 AWG	—
	Out + / -	6 AWG	—
		6 AWG	—
		—	—
		26... 16 AWG	—