

Product data sheet Characteristics

C125723

Acti9, MSC Chassis 3PH, 250A, 27mm for C120 MCB 72 poles, Dual Feed



Main	
Range	Acti9
Device short name	MSC 27
Product or component type	Chassis
Device application	Distribution

Complementary

Range compatibility	Acti 9 Acti9 Isobar B distribution board	
[In] rated current	250 A	
Short-circuit withstand	25 kA 0.1 s	
[lcw] rated short-time withstand current	25 kA	
Number of ways	1 way (incomer) - 3P 72 (outgoer)	
Outgoer Pole capacity	72 x 27 mm	
Busbar pitch	27 mm	
Length	974 mm	
Width	215 mm	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	21.5 cm	
Package 1 Width	0.1 cm	
Package 1 Length	116.3 cm	
Package 1 Weight	7.9 kg	

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	☑ China RoHS Declaration
Circularity Profile	No need of specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.