

## Product data sheet Characteristics

# C3DC723

## Acti9, MSC DC Chassis for iC60 1PH 250A 72P

Main	
Range	Acti9
Device short name	MSC DC
Product or component type	Chassis
Device application	Distribution

#### Complementary

Range compatibility	Acti 9 Acti9 Isobar A distribution board	
[In] rated current	250 A	
[lcw] rated short-time withstand current	25 kA	
Short-circuit withstand	25 kA 0.1 s	
Number of ways	1 way (incomer) - 2P 72 (outgoer)	
Number of poles	72 x 18 mm	
Width	215 mm	
Length	650 mm	
Busbar pitch	18 mm	

#### Packing Units

- doming of the		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	5.126 kg	

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	Ğ China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.