

Product data sheet

Characteristics

EY56C532

Easy56, Switched Socket, 5 Pin, 32A, 500V



Main

| | |
|---------------------------|--------------------------|
| Product name | Easy56 |
| Product or component type | Switch and socket-outlet |
| Device short name | EY56C532 |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Control type | Rotary knob |
| Rotary handle padlocking | 2 padlocks 8 mm |
| Network type | AC |
| Outlet standard deviation | Australian/New Zealand |

Complementary

| | |
|-------------------------------------|---|
| Mounting mode | Surface mounted |
| Plug, socket, control station shape | Straight |
| [In] rated current | 32 A |
| Pin number | 5 pins |
| Shape of pin | Tubular |
| [Ue] rated operational voltage | 500 V |
| Network frequency | 50 Hz |
| Protection type | Without protection |
| Material | Polycarbonate |
| Contacts material | Pins: brass |
| Connections - terminals | Screw terminals |
| Cable cross section | 1...16 mm ² |
| Cable entry number | 2 x M25 1 x M32 |
| Net weight | 0.82 kg |
| Height | 203 mm |
| Width | 101 mm |
| Depth | 101 mm |
| Colour | Body: grey (RAL 7035) Rotary handle: dark grey |

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | AS/NZS 3123 AS/NZS 3133 |
| IP degree of protection | IP66 conforming to AS 60529 |
| Ambient air temperature for operation | -25...75 °C |
| Ambient air temperature for storage | -25...75 °C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.4 cm |
| Package 1 Width | 10.8 cm |
| Package 1 Length | 21.0 cm |
| Package 1 Weight | 944.0 g |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |