

Product data sheet Characteristics

ISM11355

OptiLine 70 - wall/ceiling frame - PC/ABS aluminium metallic



Main OptiLine 70 Range of product Cabling installation Trunking system Product type Wall/ceiling frame Colour Aluminium metallic Quantity package 1 / Set of 1 unit

Complementary

Trunking material	Aluminium	
Trunking dimension	120 x 55 mm	
Fixing mode	Snap-fitted	-
Product material	PC/ABS painted	
Length	22 mm	
Height	175 mm	
Width	82 mm	

Environment

Standards	73/23/EEC	
	93/68/EEC	
	EN 50085-1:2005	
	EN 50085-1:2013/A1	
	EN 50085-2-1:2006	
	EN 50085-2-1:2011/A1	
	NF C 68-102	
Operating temperature	-2560 °C	
IP degree of protection	IP40	
IK degree of protection	IK07	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	17.5 cm	
Package 1 Width	8.2 cm	
Package 1 Length	2.2 cm	
Package 1 Weight	30.0 g	
Unit Type of Package 2	PAL	
Number of Units in Package 2	480	
Package 2 Height	45.0 cm	
Package 2 Width	80.0 cm	
Package 2 Length	120.0 cm	
Package 2 Weight	32.168 kg	

Unit Type of Package 3	BAG	
Number of Units in Package 3	60	
Package 3 Height	30.0 cm	
Package 3 Width	29.9 cm	
Package 3 Length	39.8 cm	
Package 3 Weight	2.521 kg	

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months	

Life Is On