

## Product data sheet

### Characteristics

# KBC10DCB40

## 10A TAPOFF UNITS



### Main

Range	Canalis
Product or component type	Tap-off unit
Device short name	KBC
Product compatibility	KBA KBB
Device application	Lighting
Range compatibility	KBB busbar trunking KBA busbar trunking

### Complementary

[Ue] rated operational voltage	230...240 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	10 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Busbar trunking polarity	L + N + PE L2 + L1 + L3 + N + PE
Tap-off unit polarity	To be defined 3L+N+PE
Tap-off unit connector type	With phase selection
Standards	EN/IEC 61439-6 EN/IEC 60439-2
Width	1 m
Depth	62 mm
Height	60 mm
Colour	Cream (RAL 9001)
Net weight	65 g
Quantity per set	Set of 10

### Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	86.9 g
Package 1 Height	6 cm
Package 1 width	6.2 cm
Package 1 Length	11.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	880 g
Package 2 Height	12.5 cm

Package 2 width	14 cm
Package 2 Length	32 cm
Unit Type of Package 3	P06
Number of Units in Package 3	300
Package 3 Weight	34.9 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	60 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months
----------	-----------

