

## Product data sheet

### Characteristics

# L5103D20UAR1

## C-Bus-3 channel 20A architectural dimmer-with 1 RCD-universal



### Main

Range	C-Bus
Product or component type	Dimmer
Device application	Control
Load type	Incandescent: 20 W (minimum)
Provided equipment	RCCB, 4
Number of channels	3

### Complementary

Maximum leakage current	10 mA
[Us] rated supply voltage	240 V AC 47...53 Hz 415 V AC 47...53 Hz
Starting time	0.5 s
Rated breaking capacity	6 kA
[Ui] rated insulation voltage	500 V

### Environment

Dielectric strength	2500 V
Directives	2004/108/EC - electromagnetic compatibility
Standards	EN 61000-3-3 AS/NZS CISPR 15 EN 61000-3-5 IEC 60669-2-1 EN 55015 EN 55014-1 AS/NZS CISPR 14-1 AS/NZS 3439-1 EN 61000-3-11 EN 61000-3-2 IEC 60439-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	11.0 kg
Package 1 Height	61.8 cm
Package 1 width	29.4 cm
Package 1 Length	37 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>