

Product data sheet Characteristics

L5508D1A

Clipsal C-Bus, Dimmer, DIN Rail Mounted, Leading Edge, 240V AC, 8 Channel, 1A, With **C-Bus Power Supply**



Range	C-Bus
Product brand	Clipsal
Product or component type	Dimmer
Device application	Control
Device presentation	Basic element
Load type	Incandescent Low voltage lamp with electronic transformer
Load current	1 A per channel
Dimmer type	Leading edge
Power supply output current	200 mA

Complementary

complementary	
Standby consumption	10 W
Network frequency	4753 Hz
	5763 Hz
Communication network type	C-Bus
Maximum number of supported devices	10 per network
Input impedance	50 kOhm at 1 kHz
Isolation voltage	3.75 kV from C-Bus to mains
Starting time	5 s
Time delay range	033.5 min
Software function	Select network clock
	Select network burden
	Select time delay range
Number of modules	12
Local signalling	LED
Number of channels	8
Connector type	RJ45 for C-Bus
71	RJ45 for remote override
Mounting support	DIN rail
Clamping connection capacity	1 x 2.5 mm²
	2 x 1.5 mm ²
Width	215 mm
Height	85 mm
Depth	65 mm
Net weight	675 g

Environment

Ambient air temperature for operation	045 °C
Relative humidity	1095 %

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	9.6 cm	
Package 1 Width	11.0 cm	
Package 1 Length	22.8 cm	
Package 1 Weight	786.0 g	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	[™] End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Life Is On