

Product data sheet Characteristics

NSYS3D10630P

Spacial, Wall mounted steel enclosure, Spacial S3D, plain door, with mounting plate, 1000x600x300mm, IP66, IK10





Main Range Spacial Product name Spacial S3D Application Multi-purpose Category Compact enclosure 1000 mm **Enclosure nominal** height Enclosure nominal width 600 mm **Enclosure nominal** 300 mm depth Door type Plain Mounting plate Plain description Type of gland plate Standard Wall-mounting Installation accessory type

1 body

1 mounting plate 1 door with lock 1 cable gland plate

Complementary

Body type	Single piece body
	Gutter-shaped front rail double sheet thickness
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges Cable gland plate by screws
	Mounting plate by fixing element
Material	Enclosure: steel
	Mounting plate: galvanised steel
Surface finish	Enclosure: epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	DNV
	GL
	BV
	CUL
	UL
	LR
Net weight	41 kg

Device composition

Environment

NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK10 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	36.0 cm
Package 1 Width	62.0 cm
Package 1 Length	103.0 cm
Package 1 Weight	36.6 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	6
Package 2 Height	139.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	233.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	☐ Product Environmental Profile

Contractual warranty

Warranty	18 months