


Product data sheet Characteristics

R5062VNL

C-Bus, Reflection Wall Switches, 2 Gang





Main

Tricking and the second	
Product brand	Clipsal
Device presentation	Basic element with full cover plate

Complementary

Control type	Button
[Ue] rated operational voltage	1536 V DC
[In] rated current	20 mA
Mounting support	Wall

Packing Units

1 doking office		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.7 cm	
Package 1 Width	9.2 cm	
Package 1 Length	13.5 cm	
Package 1 Weight	218 g	
Unit Type of Package 2	CAR	
Number of Units in Package 2	25	
Package 2 Height	23.5 cm	
Package 2 Width	25.1 cm	
Package 2 Length	29.6 cm	
Package 2 Weight	6.1 kg	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information

Life Is On