

Product data sheet

Characteristics

WMB532

Metal Clad, Socket Outlet 1 Gang, 32A, 500V,
5 Round Sockets, Cast Aluminium



Main

Range of product	Wilco
Product brand	Clipsal

Complementary

Device mounting	Surface
Mounting mode	External mounting
[In] rated current	32 A
[Ue] rated operational voltage	500 V 50/60 Hz conforming to EN 60309-2
Voltage colour	Black
Duration	7 h
Material	Cast aluminium
Socket number	1
Socket-outlet type	S
Depth	110 mm
Width	115 mm
Height	150 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.0 cm
Package 1 Width	11.5 cm
Package 1 Length	15.0 cm
Package 1 Weight	1055.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	9
Package 2 Height	26.2 cm
Package 2 Width	27.3 cm
Package 2 Length	33.4 cm
Package 2 Weight	9495.0 g

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations