5000ETP10W

C-Bus Control and Management System,
Ethernet Touch Panel. Price On Application

Green Premium™

Main

Range	C-Bus
Product or component type	Touch panel
Device application	Equipment monitoring and control
Display colour	262000 colours
Display size	10.1 inch
Provided equipment	1 mounting plate 1 cover frame 10 fixing screws 4 washer 1 screw 1 desk stand 1 micro SD card securing plate 1 Ethernet cable securing plate
Cover frame colour tint	White

Complementary

Supply	External power supply: 12 V DC, +/- 5 %, <1.5 A Via PoE: - 15 W
Maximum power consumption in W	6 W typical
Standby consumption	< 0.5 W
Display resolution	1280 x 800 pixels
Brightness	300 cd/m²
View angle horiz x vert	170° horizontal 170° vertical
Communication port protocol	Ethernet
Port Ethernet	10/100BASE
Integrated connection type	Ethernet port USB port HDMI Micro SD card port Audio output
Connector type	Power input
Contrast ratio	800:1
Aspect ratio	16:9
Response time	30 ms typical
Mounting location	Wall mounting
Device mounting	Flush Surface
Width	Cover frame: 316 mm
Height	Cover frame: 220 mm
Depth	Cover frame: 6 mm

Environment

Ambient air temperature for operation	0…40 °C
Relative humidity	10…85 %
Standards	IEEE 802.3af

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.5 cm
Package 1 Width	23.0 cm
Package 1 Length	35.0 cm
Package 1 Weight	1.55 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Height	38.0 cm
Package 2 Width	24.5 cm
Package 2 Length	43.5 cm
Package 2 Weight	6.2 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins