

# Product data sheet

## Characteristics

# 5031NMMIRL

## Master Mechanism, C-Bus Control and Management System, IR Capable



### Main

Range of product	Series 30M
Product brand	Clipsal
Product or component type	IR capable master mechanism

### Complementary

Range compatibility	C-Bus
Device mounting	Wall mounted by Series 30M grid
[Ue] rated operational voltage	15...36 V DC
Input impedance	100 kOhm at 1 kHz
Local signalling	LED (blue/orange) for status
Suitable cable type	Twisted unshielded pairs cable category 5e
Isolation voltage	3.75 kV from C-Bus to mains
Communication network type	C-Bus

### Environment

Relative humidity	10...95 % non-condensing
-------------------	--------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 cm
Package 1 Width	6.4 cm
Package 1 Length	10 cm
Package 1 Weight	54 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes

