

## Product data sheet

### Characteristics

# 755PFM4

## Photoelectric Smoke Alarm FireTek - Flush mount - 240 V mains-powered - 9V battery backup



### Main

Range	Fire Tek
Product brand	Clipsal
Product or component type	Smoke detector
Device application	Early detection of smouldering fires and open fires
Electronic sensor type	Photo-electric sensor
Colour	White (RAL 9003)
Quantity per set	Set of 1
Type of packing	Carton

### Complementary

Supply	Mains
[Us] rated supply voltage	220...240 V AC 50 Hz
Backup type	Battery
Battery type	Alkaline 9 V 6LR61
Battery life	1 year(s)
[In] rated current	13 mA: 9 V DC not in operation 40 mA: 9 V DC operation
Output voltage limits	Interconnection: 6.5...20 V
Type of alarms	Low battery at 6.9...7.5 V
Detection type	Smoke
Device composition	1 smoke detector 1 mounting base 1 dust protection foil 1 user guide 3 screws 1 sticker sheet
Function available	Local alarm Hush function Self-test of smoke detection
Technology type	Scattered light (Tyndall effect)
Type of measurement	Optic
Maximum number of device interconnected	40 for wired alarm wired over <= 150 m
Horn level	85 dB at 3 m, minimum
Local signalling	Sound: signal Visual: LED (red) for warning and low battery Visual: LED (green) for ON status
Connections - terminals	Screw terminal (line) - 2 x 1...3 x 2.5 mm <sup>2</sup> Screw terminal (neutral) - 2 x 1...3 x 2.5 mm <sup>2</sup> Screw terminal (earth loop) - 2 x 1...3 x 2.5 mm <sup>2</sup> Screw terminal (interconnect) - 2 x 1...3 x 2.5 mm <sup>2</sup>
Material	PC (polycarbonate)
Type of installation	Indoor
Device mounting	Flush
Mounting support	Ceiling

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Fixing mode	By screws
Diameter	108 mm
Depth	102.6 mm
Projecting depth	23 mm
Net weight	263 g

## Environment

IP degree of protection	IP20
Ambient air temperature for operation	0...45 °C
Relative humidity	5...95 %
Product certifications	RCM SAI Activfire
Standards	ISO 8201 AS 3786:2014 AS/NZS 60950.1 AS/NZS 60065

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	343.0 g
Package 1 Height	10.6 cm
Package 1 width	14.5 cm
Package 1 Length	14.5 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>