

Product data sheet Characteristics

NSYDPLA105G PLA door 1000x500





Main

| Range | Thalassa |
|------------------------------------|--------------------------|
| Accessory / separate part category | Enclosure accessory |
| Product or component type | Door |
| Application | Multi-purpose |
| For enclosure nominal dimensions | - |
| Mounting location | Front |
| Range compatibility | Thalassa Thalassa PLA |
| Device composition | 1 door Locking system |
| Quantity per set | Set of 1 |

Complementary

| Material | Door: polyester reinforced with fibreglass |
|-------------------|--|
| Colour | Door: grey (RAL 7035) |
| Lock type | Lock 5 mm double bar |
| Number of locks | 1 |
| Door type | Plain |
| Door opening side | Reversible (120 °) Reversible (180 °) |
| Maximum load | 30 kg/m² |
| Height | 1000 mm |
| Width | 500 mm |

Packing Units

| 3 | | |
|------------------------------|----------|--|
| Unit Type of Package 1 | PCE | |
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 79.0 cm | |
| Package 1 Width | 6.0 cm | |
| Package 1 Length | 105.0 cm | |
| Package 1 Weight | 5.95 kg | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|--|--|
| REACh Regulation | ☑REACh Declaration | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) | |
| Mercury free | Yes | |
| China RoHS Regulation | ☑ China RoHS Declaration | |
| RoHS exemption information | ₫Yes | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | No need of specific recycling operations | |

