

Product data sheet Characteristics

PDL5011WSZ

Product or component

type

Micro Module Switch, Wiser, 10 AX, 240 V, Grey





Main Range compatibility Wiser hub Product brand PDL Range Iconic

Connected switch

Complementary

Device presentation	Module	
Technology type	Electronic	
Load type	Dimmable LED lighting driver: 10 A LED lighting driver (non-dimmable): 10 A Electronic transformer: 10 A Medium voltage halogen lamp: 10 A Linear fluorescent ballast: 10 A Inductive: 6 A (cos phi =0.6) Resistive: 15 A Motor: 10 A	
[Ue] rated operational voltage	220240 V AC 50 Hz	
Protection type	Over temperature protection Thermal protection	
Colour tint	Grey	
Control type	Push-button By mobile application	
Software name	Wiser by SE App	
Technology type	Zigbee	
Wiring configuration	3-wire	
Material	Plastic	
Mounting support	Wall Installation box	
Type of installation	Indoor installation	

Environment

Relative humidity	590 % non-condensing	
Standards	AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information

