

Product data sheet Characteristics

PDL640RC

4-Gang Mounting Block With Round Conduit; White





Main

Range of product	PDL General Accessories
Product or component type	Mounting plate
Colour tint	White
Quantity per set	Set of 5
Type of packing	Carton

Complementary

Material	PC (polycarbonate)	
Surface finish	Glossy	
Installation direction	Horizontal	
Device mounting	Surface	
Height	84 mm	
Width	196 mm	
Depth	19 mm	
Fixing center	84 mm	
Number of gangs	4 gangs	
Cable entry	7 x 20 mm knock-out	

Environment

Ambient air temperature for operation	-1040 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	8.5 cm
Package 1 Length	20.0 cm
Package 1 Weight	0.081 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	12 cm
Package 2 Width	15.6 cm
Package 2 Length	19.5 cm
Package 2 Weight	473.0 g
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	20.8 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 3 Width	31.7 cm	
Package 3 Length	62.1 cm	
Package 3 Weight	4730.0 g	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

