# A9KS15263BQ

## Acti 9K Isolator 2P 63A 415Vac - set of 6





#### Main

Range	Acti9
Product name	Acti9 SW
Product or component type	Switch disconnector
Device short name	SW
Device application	Control
Poles description	2P
Utilisation category	AC-22A

### Complementary

[le] rated operational current	63 A at 415 V AC 50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
Quantity per set	Set of 6
[lcm] rated short-circuit making capacity	0.9 kA switch-disconnector alone
[lcw] rated short-time withstand current	756 A during 300 ms
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-3
Control type	Toggle
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Downstream: biconnect
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	74 mm
Net weight	0.24 kg
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Connections - terminals	Tunnel type terminals (downstream) - 135 mm² - rigid Tunnel type terminals (downstream) - 125 mm² - flexible Tunnel type terminals (upstream) - 135 mm² - rigid Tunnel type terminals (upstream) - 125 mm² - flexible
Wire stripping length	9 mm
Tightening torque	3.5 N.m

### Environment

Standards	IEC 60947-3	
IP degree of protection	IP20 IP40	
Pollution degree	2	
Tropicalisation	2	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-555 °C	
Ambient air temperature for storage	-2585 °C	

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.8 cm	
Package 1 Width	10.6 cm	
Package 1 Length	24.2 cm	
Package 1 Weight	979 g	

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EEEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫ <sub>Yes</sub>
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information