



### Main

Range of product	Acti9
Product name	Acti9 MIN
Device short name	MIN
Product or component type	Electromechanical timer
Colour tint	White (RAL 9003)

### Complementary

Device application	Building
Load type	Parallel-corrected fluorescent tube 14 x 40 W 4.7 µF Parallel-corrected fluorescent tube 10 x 58 W 7 µF Parallel-corrected fluorescent tube 3.0 x 100 W 18 µF 230 V AC halogen lamp 2300 W 230 V AC incandescent lamp 2300 W Fluocompact lamp 2300 VA Compact fluorescent lamp 21 x 7 W Compact fluorescent lamp 13 x 11 W Compact fluorescent lamp 10 x 15 W Compact fluorescent lamp 7 x 20 W LED lamp < 2 W 30 W LED lamp > 2 W 300 W
Power consumption in VA	1 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V AC at 50 Hz
Time delay	Adjustable from 1 to 7 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals - ≤ 6 mm²
Width	18 mm
Height	83 mm
Depth	68 mm
Net weight	84 g

### Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP20 B

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2 cm
Package 1 Width	7 cm
Package 1 Length	9.9 cm
Package 1 Weight	82 g

Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.5 cm
Package 2 Width	10.5 cm
Package 2 Length	22 cm
Package 2 Weight	865 g
Unit Type of Package 3	S03
Number of Units in Package 3	110
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	10.033 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------