EVB1A22PCRI

EVlink Smart Wallbox - 22 kW - Attached cable T2 - RFID





Main	
Range	EVlink
Product name	EVlink Smart Wallbox
Product or component type	Charging station
Device short name	EVB1
Poles description	3P + N for power circuit
Mounting mode	Wall-mounted Pedestal mount
Offer type	Standard
Rated supply voltage	380415 V AC 50/60 Hz
Max power	22 kW 32 A 380415 V
Access control system	Badge RFID conforming to ISO/IEC 14443 A and B Badge RFID conforming to ISO/IEC 15693 Badge RFID conforming to ISO 14443-4 A

Complementary

Socket-outlet number	1	
Output type	Right side T2 attached cable / silver plated contacts 4.5 m	
Earthing system	TT Compatible IT with additional isolation transformer on the power supply TN-S	
Number of inputs	6	
Connector type	RS485 for metering Modbus 3 RJ45 for Ethernet LAN connection	
Input type	Binary for power limitation closing contact Binary for delayed charging closing contact	
Control type	Can be controlled by remote 1 multi-colour illuminated push-button, function: stop/restart	
Local signalling	1 multi-colour LED, function: status indication	
Communication port protocol	OCPP 1.6	
Configuration /Architecture	Standalone Clustered architecture	
Operation and maintenance	Charge detail records Diagnosis capabilities Load management	
Web server	Embedded	
Ethernet service	Configuration via web server	
Height	480 mm	
Width	330 mm	
Depth	170 mm	

Environment

Standards	IEC 61851-22	
	IEC 61851-1	
	IEC 62196-2	
	IEC 62196-1	
Product certifications	CE[RETURN]CB[RETURN]RCM	
IP degree of protection	IP54 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Ambient air temperature for operation	-3050 °C	

Ambient air temperature for storage	-4080 °C
Relative humidity	595 %
Net weight	8.3 kg
Colour	White (RAL 9003) Grey (RAL 7016)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.000 cm
Package 1 Width	40.000 cm
Package 1 Length	54.000 cm
Package 1 Weight	10.800 kg
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	51.908 kg

Offer Sustainability

Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	☐ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	