
Product data sheet Characteristics

LV429345

auxiliary contact - 1 OC early-break - for NSX100..250



Main	
Range of product	ComPact NSX100250 ComPact NSX100250 DC
Range	ComPact
Device short name	early-break contact
Product or component type	Auxiliary contact
Device application	Control
Range compatibility	ComPact ComPact NSX100 ComPact ComPact NSX160 ComPact ComPact NSX250 ComPact Compact NSX100 DC ComPact Compact NSX160 DC ComPact Compact NSX250 DC PowerPact PowerPact H PowerPact PowerPact J

Complementary

Auxiliary contacts type	Standard	
Auxiliary contacts operation	Early-break	
Mounting mode	Drawout	
[Ith] conventional free air thermal current	6 A	
[le] rated operational current	AC-12: 6 A at 110 V AC 50/60 Hz	
	AC-12: 6 A at 220/240 V AC 50/60 Hz	
	AC-12: 6 A at 24 V AC 50/60 Hz	
	AC-12: 6 A at 380/440 V AC 50/60 Hz	
	AC-12: 6 A at 48 V AC 50/60 Hz	
	AC-12: 6 A at 480 V AC 50/60 Hz	
	AC-12: 6 A at 660/690 V AC 50/60 Hz	
	AC-15: 0.1 A at 660/690 V AC 50/60 Hz	
	AC-15: 1.5 A at 480 V AC 50/60 Hz	
	AC-15: 2 A at 380/440 V AC 50/60 Hz	
	AC-15: 4 A at 220/240 V AC 50/60 Hz	
	AC-15: 5 A at 110 V AC 50/60 Hz	
	AC-15: 6 A at 24 V AC 50/60 Hz	
	AC-15: 6 A at 48 V AC 50/60 Hz	
	DC-12: 0.3 A at 250 V DC	
	DC-12: 0.6 A at 110 V DC	
	DC-12: 2.5 A at 48 V DC	
	DC-12: 6 A at 24 V DC	
	DC-14: 0.03 A at 250 V DC	
	DC-14: 0.05 A at 110 V DC	
	DC-14: 0.2 A at 48 V DC	
	DC-14: 1 A at 24 V DC	
Minimum load	100 mA at 24 V DC	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.0 cm	
Package 1 Width	6.2 cm	
Package 1 Length	8.0 cm	
Package 1 Weight	49.0 g	
Unit Type of Package 2	S03	
Number of Units in Package 2	45	
Package 2 Height	30.0 cm	
Package 2 Width	30.0 cm	

16 May, 2024

Package 2 Length	40.0 cm
Package 2 Weight	2.512 kg
Offer Sustainability	
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	[☑] China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Contractual warranty	
Warranty	18 months