LV429382

shunt trip voltage release MX - 12 V DC





Main

Range	ComPacT
Range of product	ComPact NSX100250 ComPacT NSX100250 new generation ComPact NSX400630 ComPacT NSX400630 new generation ComPact NSX100250 DC ComPacT NSX100250 DC new generation ComPact NSX100250 DC PV ComPacT NSX100250 DC PV ComPacT NSX100250 DC PV new generation ComPact NSX400630 DC ComPacT NSX400630 DC ComPact NSX400630 DC PV ComPacT NSX400630 DC PV ComPacT NSX400630 DC PV
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Shunt trip release
[Uc] control circuit voltage	12 V DC
Range compatibility	ComPacT new generation ComPacT NSX new generation ComPacT new generation ComPacT NSX DC new generation ComPact ComPact NSX ComPact ComPact NSX DC EasyPact EasyPact CVS PowerPact PowerPact Multistandard

Complementary

Operating threshold	0.71.1 x Un opening
Response time	50 ms
Control signal type	Maintained Impulse
Impulse duration	>= 20 ms
Supply inrush power	10 W
Auxiliary connection terminal	Spring 0.51.5 mm² (AWG 20AWG 16)
Wire stripping length	7 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	4 cm
Package 1 Length	8.5 cm
Package 1 Weight	123 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.2 cm
Package 2 Width	14.7 cm
Package 2 Length	22.5 cm
Package 2 Weight	1.31 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not interested for a set of or determining suitability or intelability of these products for specific user applications. It is the documentation is not integrator to perform the appropriate and complete risk analysis, evaluating of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Unit Type of Package 3	S03	
Number of Units in Package 3	60	
Package 3 Height	30 cm	
Package 3 Width	30 cm	
Package 3 Length	40 cm	
Package 3 Weight	8.35 kg	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months