RSZE1S48M

socket RSZ - separate contact - < 250 V AC - screw connector





Main

Range of product	Harmony Electromechanical Relays
Device short name	RSZ
Product or component type	Socket
Product compatibility	Plug-in relay RSB with 1 C/O contact at 16 A Plug-in relay RSB with 2 C/O contact at 8 A
Contacts type and composition	2 C/O
[lth] conventional free air thermal current	10 A

Complementary

Observator	Flor
Shape of pin	Flat
[Ue] rated operational voltage	< 250 V AC
Contact terminal arrangement	Separate
Connections - terminals	Screw connectors, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end
	Screw connectors, 2 x 0.252 x 1 mm ² (AWG 22AWG 17) flexible with cable end
	Screw connectors, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end
	Screw connectors, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable
	end
Tightening torque	< 0.8 N.m for M3 screw(s)
Fixing mode	By screw (panel)
	Clip-on (35 mm symmetrical DIN rail)
[Uimp] rated impulse withstand voltage	3.6 kV
Overvoltage category	III
Pollution degree	3
Sale per indivisible quantity	10
Width	15.5 mm
Net weight	0.05 kg

Environment

IP20 conforming to IEC 60529
IEC 61984
CSA[RETURN]UL
CE
-4085 °C
-2585 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.700 cm	
Package 1 Width	6.200 cm	
Package 1 Length	8.000 cm	

Package 1 Weight	39.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.000 cm
Package 2 Width	9.000 cm
Package 2 Length	17.000 cm
Package 2 Weight	428.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	240
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	10.575 kg


Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months


Dimensions



- (1) Relays
- (2) Protection module
- (3) Maintaining clamp
- (4) Legend

Wiring Diagram





(1) Terminals 11 and 21,14 and 24,12 and 22 must be linked for this references NOTE: For DC input, A1 have to be +, otherwise it would short circuit from protection module