Product data sheet Characteristics

VW3M1C20R30 LXM28 STO connection cable 3m



Main	
Range of product	Lexium 28
Product or component type	Safe torque off cable
Accessory / separate part type	Preassembled STO cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo drive LXM28
Accessory / separate part destination	Between servo drive and logic controller
Range compatibility	Lexium 28
Cable length	3 m

Complementary

Electrical connection	Connector - Molex 4-pin for servo drive side Free end for CN9 interface
Net weight	0.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.000 cm
Package 1 Width	28.000 cm
Package 1 Length	28.000 cm
Package 1 Weight	177.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.090 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
PVC free	Yes