

# Product data sheet

## Characteristics

# VW3M5D1FR50

power cable 5m shielded 4x 0,82mm<sup>2</sup>, BCH2  
brake leads connection



### Main

Range of product	Lexium 28
Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BCH2 at 50 W (40 mm) (with brake) Servo motor BCH2 at 100 W (40 mm) (with brake) Servo motor BCH2 at 200 W (60 mm) (with brake) Servo motor BCH2 at 400 W (60 mm) (with brake) Servo motor BCH2 at 400 W (80 mm) (with brake) Servo motor BCH2 at 750 W (80 mm) (with brake)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 28
Cable length	5 m

### Complementary

Electrical connection	Free end for servo drive side Connector - Molex 6-pin for servo motor side
AWG gauge	6 x AWG 18
Net weight	0.45 kg

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 cm
Package 1 Width	33 cm
Package 1 Length	36 cm
Package 1 Weight	864 g
Unit Type of Package 2	S02
Number of Units in Package 2	4
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.76 kg

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
PVC free	Yes