



Main

Range of product	Lexium
Accessory / separate part category	Connection accessory
Accessory / separate part type	Encoder cable
Product or component type	Cable
Accessory / separate part destination	From servo motor to servo drive
Cable composition	3 x (2 x 0.2 mm ²) + (2 x 0.5 mm ²)

Complementary

Product compatibility	Servo motor BCH16 40 mm, 0.1 kW, with brake Servo motor BCH16 40 mm, 0.1 kW, without brake Servo motor BCH16 60 mm, 0.2 kW, with brake Servo motor BCH16 60 mm, 0.2 kW, without brake Servo motor BCH16 60 mm, 0.4 kW, with brake Servo motor BCH16 60 mm, 0.4 kW, without brake Servo motor BCH16 80 mm, 0.75 kW, with brake Servo motor BCH16 80 mm, 0.75 kW, without brake Motion servo drive LXM16D, 0.1 kW, 200...230 V Motion servo drive LXM16D, 0.2 kW, 200...230 V Motion servo drive LXM16D, 0.4 kW, 200...230 V Motion servo drive LXM16D, 0.75 kW, 200...230 V
Electrical connection	1 connector 9-position TE connector 9 pin(s) 1 connector Firewire 10 pin(s)
Range compatibility	Easy Lexium 16
Type of cable	Shielded cable
Cable length	5 m
Net weight	0.32 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.0 cm
Package 1 Width	35.0 cm
Package 1 Length	2.3 cm
Package 1 Weight	410.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.541 kg