XVS72BMBN

Electronic alarm, Harmony XVS, black, NPN, mounting support DIN 72, 0...90dB, 16tones, 4 channels, 12...24V AC DC





Main	
Range of product	Harmony XVS
Product or component type	Electronic alarm
Device short name	XVS

Complementary

Complementary		
Colour	Black	
Material	ABS (acrylonitrile butadiene-styrene): body PC (polycarbonate): terminal cover	
Marking	CE	
Overvoltage category	Class II conforming to IEC 61140	
Mounting support	72 mm DIN rail	
[Us] rated supply voltage	1224 V DC	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	117 mA at 12 V 125 mA at 24 V 158 mA at 12 V 200 mA at 24 V	
Clamping connection capacity	<= 1 x 1.5 mm²	
Width	72 mm	
Height	72 mm	
Depth	69.3 mm	
Net weight	0.18 kg	

Environment

Discrete output type	NPN	
Signalling type	16 tones alarm	
Standards	UL 464 IEC 61000-6-3 IEC 61000-6-2	
Product certifications	UR	
Protective treatment	TC	
Ambient air temperature for storage	-3570 °C	
Ambient air temperature for operation	-1050 °C	
IP degree of protection	Panel mounted: IP54 conforming to IEC 60529	
Noise level	090 dB (continuous or intermittent tone) at 1 m	

Packing Units

PCE
1
9.4 cm
9.4 cm
10.41 cm
0.27 kg
S03
16
30 cm
30 cm
40 cm
5.118 kg
PAL
128
60 cm
80 cm
128 cm
34.56 kg

Offer Sustainability

Green Premium product
REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
China RoHS Declaration
₫Yes
Product Environmental Profile
☑ End Of Life Information

Contractual warranty

Warranty	18 months

Product data sheet Dimensions Drawings

XVS72BMBN

Electronic Alarm

Dimensions

