

# Product data sheet Characteristics

# **A9XPH212**

Acti 9 - comb busbar - 1L+N - 18 mm pitch - 12 modules - 100 A





Main	
Range	Acti9
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part categor	Connection accessory
Lines description	1L + N
Length in 18 mm modules	12

### Complementary

Number of ways	6 ways N + 1 L	
Poles configuration for 1 way	1 x 1P + N 1 x 2P	
Connection pitch	18 mm	
Connector type	Tooth	
Distance between way	36 mm	
Marking	N L	
Insulation	Insulated	
Device presentation	Cuttable	
[le] rated operational current	100 A at 40 °C	
[Ue] rated operational voltage	415 V AC	
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2	
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal	
9 mm pitches	24	
Width	220 mm	
Colour	White (RAL 9003)	
Range compatibility	Acti 9 Acti9 iC60 Acti 9 Acti9 iK60 Acti 9 Acti9 iID Acti 9 Acti9 iID K Acti 9 Acti9 iSW Acti 9 Acti9 iSW-NA Multi9 Multi9 C60	

#### **Environment**

Standards	IEC 60947-7-1 IEC 61439-2	
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1	
Pollution degree	3 conforming to IEC 60947-7-1	
IP degree of protection	IP20 with end-pieces and tooth covers	

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.000 cm
Package 1 Width	3.000 cm
Package 1 Length	21.400 cm
Package 1 Weight	79.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	6.200 cm
Package 2 Width	8.800 cm
Package 2 Length	24.800 cm
Package 2 Weight	460.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	80
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	7.821 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------