Product data sheet Characteristics

E8215USB_WE_G12

13A 1 Gang Switched Socket with 2.1A USB, White

Main Range Pieno Product or component type Power socket-outlet + USB charger Device presentation Mechanism Socket additional information Shuttered Colour tint White Load type No inductive load

| Comple | ementary |
|--------|----------|
|--------|----------|

| Complementary | |
|--------------------------------|---|
| Socket number | 1 |
| Device mounting | Flush 47 mm |
| Switch function | ON/OFF power-socket outlet |
| Number of power socket outlets | 1 x 2P + E with shutters, British |
| Rated current | Power circuit: 13 A 220250 V, AC, 50/60 Hz |
| Surface finish | Glossy |
| Surface treatment | Untreated |
| Number of gangs | 1 gang |
| Connector type | USB type A |
| [Ue] rated operational voltage | 220250 V AC 50/60 Hz |
| Maximum power consumption in W | 0.075 W |
| Input power | 16 W |
| Integrated connection type | 2 USB port 5 V DC, maximum load current: 2.1 A |
| Material | Polycarbonate: grid plate Polycarbonate: cover Polycarbonate: surround Polycarbonate: dolly Nylon + GF: shutter Brass: contact plate Steel: spring Nickel steel: terminal screw |
| Protection type | USB port: over temperature protection with PWM IC circuit USB port: over voltage protection against surges with PWM IC circuit USB port: overcurrent between output phases and earth (on power up only) with PWM IC circuit |
| Shape of screw head | Cross |
| Screwdriver shape | Philips |
| Electrical connection | 3 screw terminal |
| Clamping connection capacity | 1 x 4 mm² for solid cable(s) 2 x 4 mm² for stranded cable(s) 1 x 2.5 mm² 2 x 2.5 mm² |
| Wire stripping length | 1012 mm |
| Mounting support | Mounting box conforming to BS 4662 |
| Fixing mode | By screws M3.5 x 25 mm |
| Fixing center | 60.3 mm |

| Product compatibility | Samsung XiaoMi Apple Tablet PC HW Power bank Smartphone HTC |
|-----------------------|---|
| Height | 87 mm |
| Width | 87 mm |
| Depth | 42.15 mm |
| Embedding depth | 30.1 mm |
| Net weight | 0.1064 kg |

Environment

| Operating altitude | <= 2000 m |
|---------------------------------------|--------------------------|
| Ambient air temperature for operation | 040 °C |
| Ambient air temperature for storage | -560 °C |
| Relative humidity | 095 % |
| Standards | IEC 60950-1 BS 1363-2 |
| Product certifications | IEC |
| IP degree of protection | IP20 |
| Environmental characteristic | Alcohol Liquid soap |

Packing Units

| r doming office | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.0 cm |
| Package 1 Width | 12.0 cm |
| Package 1 Length | 12.0 cm |
| Package 1 Weight | 115.0 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 8 |
| Package 2 Height | 9.5 cm |
| Package 2 Width | 15.0 cm |
| Package 2 Length | 19.0 cm |
| Package 2 Weight | 920.0 g |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 80 |
| Package 3 Height | 21.0 cm |
| Package 3 Width | 31.0 cm |
| Package 3 Length | 50.0 cm |
| Package 3 Weight | 9.2 kg |
| | |

Offer Sustainability

| Chor Cuciamasinty | |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |