



Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G duct PrismaSeT PrismaSeT P cubicle
Type of front plate	Cut-out
Type of front plate	Cut-out
Installed device	Human-switchboard interface: 96 x 96 mm device Human-switchboard interface: HSI PowerLogic: PM400...800 Enerlin'X: FDM121

Complementary

Enclosure/cubicle description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle duct - width 400 mm depth 400 mm
Number of vertical modules [50 mm]	3
Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA
Surface finish	Matt Textured
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	150 mm
Net weight	0.62 kg
Quantity per set	Set of 1
Functional unit	400 mm 400 mm PrismaSeT P cubicle human-switchboard interface 96 x 96 mm device 1 3 400 mm 400 mm PrismaSeT P cubicle human-switchboard interface HSI 1 3 400 mm 400 mm PrismaSeT P cubicle PowerLogic 1 3 300 mm PrismaSeT G floor-standing duct human-switchboard interface 96 x 96 mm device 1 3 300 mm PrismaSeT G wall-mounted duct human-switchboard interface 96 x 96 mm device 1 3 300 mm PrismaSeT G floor-standing duct human-switchboard interface HSI 1 3 300 mm PrismaSeT G wall-mounted duct human-switchboard interface HSI 1 3 300 mm PrismaSeT G floor-standing duct PowerLogic 1 3 300 mm PrismaSeT G wall-mounted duct PowerLogic 1 3 400 mm 400 mm PrismaSeT P cubicle Enerlin'X FDM121 1 3 300 mm PrismaSeT G floor-standing duct Enerlin'X FDM121 1 3 300 mm PrismaSeT G wall-mounted duct Enerlin'X FDM121 1 3

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.900 cm
Package 1 Width	16.000 cm
Package 1 Length	26.500 cm
Package 1 Weight	319.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	16.700 cm
Package 2 Width	17.400 cm
Package 2 Length	28.000 cm
Package 2 Weight	3.302 kg
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	29.500 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	64.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations