



Main

Range	Prisma
Range of product	Prisma G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	Prisma Prisma G duct
Type of rail	Modular
Installed device	<p>Acti 9: fixed C120 without earth leakage protection - control: toggle</p> <p>TeSys: fixed GV2LE</p> <p>TeSys: fixed GV2ME</p> <p>TeSys: fixed GV2RTn</p> <p>Acti 9: fixed iC120 without earth leakage protection - control: toggle</p> <p>ComPact: fixed INS100 - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed INS160 - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed INS40 - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed INS63 - control: direct front rotary handle - vertical installation</p> <p>Acti 9: fixed modular device</p> <p>Multi9: fixed modular device</p> <p>Multi9: fixed NG125 without earth leakage protection - control: toggle</p> <p>Multi9: fixed NG125 NA - control: toggle</p> <p>Acti 9: fixed C120 with earth leakage protection - control: toggle</p> <p>Acti 9: fixed iC120 with earth leakage protection - control: toggle</p> <p>Multi9: fixed NG125 with earth leakage protection - control: toggle</p> <p>ComPact: fixed INS125 - control: direct front rotary handle - vertical installation</p> <p>Acti 9: fixed modular device ≤ 40 A</p> <p>Multi9: fixed modular device ≤ 40 A</p>
Poles description	<p>1 x 3P: fixed C120</p> <p>1 x 4P: fixed C120</p> <p>1 x 3P: fixed iC120</p> <p>1 x 4P: fixed iC120</p> <p>1 x 3P: fixed INS100 vertical installation</p> <p>1 x 4P: fixed INS100 vertical installation</p> <p>1 x 3P: fixed INS160 vertical installation</p> <p>1 x 4P: fixed INS160 vertical installation</p> <p>1 x 3P: fixed INS40 vertical installation</p> <p>1 x 4P: fixed INS40 vertical installation</p> <p>1 x 3P: fixed INS63 vertical installation</p> <p>1 x 4P: fixed INS63 vertical installation</p> <p>1 x 3P: fixed NG125</p> <p>1 x 4P: fixed NG125</p> <p>1 x 3P: fixed NG125 NA</p> <p>1 x 4P: fixed NG125 NA</p> <p>1 x 3P: fixed INS125 vertical installation</p> <p>1 x 4P: fixed INS125 vertical installation</p> <p>4 x 3P: fixed GV2LE</p> <p>4 x 3P: fixed GV2ME</p> <p>4 x 3P: fixed GV2RTn</p>

Complementary

Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Number of vertical modules [50 mm]	4 module(s): C120 without earth leakage protection , direct in 300 mm Widefloor-standing duct 4 module(s): C120 without earth leakage protection , direct in 300 mm Widewall-mounted duct 3 module(s): GV2LE, direct in 300 mm Widefloor-standing duct 3 module(s): GV2LE, direct in 300 mm Widewall-mounted duct 3 module(s): GV2ME, direct in 300 mm Widefloor-standing duct 3 module(s): GV2ME, direct in 300 mm Widewall-mounted duct 3 module(s): GV2RTn, direct in 300 mm Widefloor-standing duct 3 module(s): GV2RTn, direct in 300 mm Widewall-mounted duct 4 module(s): iC120 without earth leakage protection , direct in 300 mm Widefloor-standing duct 4 module(s): iC120 without earth leakage protection , direct in 300 mm Widewall-mounted duct 4 module(s): INS100, direct in 300 mm Widefloor-standing duct 4 module(s): INS100, direct in 300 mm Widewall-mounted duct 5 module(s): INS100, direct in 300 mm Widefloor-standing duct 5 module(s): INS100, direct in 300 mm Widewall-mounted duct 4 module(s): INS125, direct in 300 mm Widefloor-standing duct 4 module(s): INS125, direct in 300 mm Widewall-mounted duct 5 module(s): INS125, direct in 300 mm Widefloor-standing duct 5 module(s): INS125, direct in 300 mm Widewall-mounted duct 4 module(s): INS160, direct in 300 mm Widefloor-standing duct 4 module(s): INS160, direct in 300 mm Widewall-mounted duct 5 module(s): INS160, direct in 300 mm Widefloor-standing duct 5 module(s): INS160, direct in 300 mm Widewall-mounted duct 4 module(s): INS40, direct in 300 mm Widefloor-standing duct 4 module(s): INS40, direct in 300 mm Widewall-mounted duct 4 module(s): INS63, direct in 300 mm Widefloor-standing duct 4 module(s): INS63, direct in 300 mm Widewall-mounted duct 3 module(s): modular device ≤ 40 A, direct in 300 mm Widefloor-standing duct 3 module(s): modular device ≤ 40 A, direct in 300 mm Widewall-mounted duct 4 module(s): modular device, direct in 300 mm Widefloor-standing duct 4 module(s): modular device, direct in 300 mm Widewall-mounted duct 4 module(s): NG125 without earth leakage protection , direct in 300 mm Widefloor-standing duct 4 module(s): NG125 without earth leakage protection , direct in 300 mm Widewall-mounted duct 4 module(s): NG125 NA, direct in 300 mm Widefloor-standing duct 4 module(s): NG125 NA, direct in 300 mm Widewall-mounted duct 4 module(s): C120 with earth leakage protection , direct in 300 mm Widefloor-standing duct 4 module(s): C120 with earth leakage protection , direct in 300 mm Widewall-mounted duct 4 module(s): iC120 with earth leakage protection , direct in 300 mm Widefloor-standing duct 4 module(s): iC120 with earth leakage protection , direct in 300 mm Widewall-mounted duct 4 module(s): NG125 with earth leakage protection , direct in 300 mm Widefloor-standing duct 4 module(s): NG125 with earth leakage protection , direct in 300 mm Widewall-mounted duct
9 mm pitches	20
Quantity per set	Set of 1
Height	52 mm
Width	218 mm
Depth	100 mm
Net weight	0.14 kg
Colour	Natural
Material	Metal

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free plastic parts product